

## **1MP IR Bullet HD Camera**

- . 1/4" 1.0MP CMOS Sensor
- . AHD/CVI/TVI/CVBS 4 IN 1
- . 2.8mm Fixed Lens
- . IR Distance max 20m
- . OSD & UTC support
- . Plastic, IP66, Outdoor/Indoor Use



| ■ SPECIFICATIONS   |                                   |
|--------------------|-----------------------------------|
| Model NO.          | HTR-1201L-S4.1                    |
| Video Output Mode  | AHD/CVI/TVI/CVBS 4 IN 1           |
| Camera             |                                   |
| Image Sensor       | 1/4" 1.0MP CMOS Sensor            |
| Image Resolution   | 1MP 720P/ 960H                    |
| Effective Pixels   | 1280*720                          |
| TV System          | PAL/NTSC                          |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s |
| S/N Ratio          | ≥50dB                             |
| Scanning System    | Progressive Scan                  |
| Lens               |                                   |
| Focus Length       | 2.8mm                             |
| Focus Control      | Fixed                             |
| Lens Type          | Fixed                             |
| Pixels             | 2M Pixels                         |
| Auto Iris Support  | NO                                |
| Night Vision       | <u> </u>                          |
| Infrared LED       | 14μ x 18PCS                       |

| Infrared Distance     | 20M                        |  |
|-----------------------|----------------------------|--|
| IR Status             | Under 10 Lux by CDS        |  |
| IR Power On           | CDS Auto Control           |  |
| Camera Features       |                            |  |
| Starlight             | /                          |  |
| Day/Night             | YES                        |  |
| OSD Menu Language     | YES                        |  |
| White Balance         | AUTO / MANUAL              |  |
| Gain Control          | AUTO                       |  |
| Noise Reduction       | DNR                        |  |
| Picture Adjustment    | YES                        |  |
| WDR                   | YES                        |  |
| OSD Support           | YES                        |  |
| итс                   | YES                        |  |
| Dip Switch            | Optional                   |  |
| General               |                            |  |
| Housing               | Plastic, IP66              |  |
| Bracket               | YES                        |  |
| Dual Voltage          | NO                         |  |
| IR Cut Filter         | YES                        |  |
| Heater                | NO                         |  |
| Audio                 | /                          |  |
| Operation Temperature | -10°C ~ +50°C RH95% Max    |  |
| Storage Temperature   | -20°C ~ +60°C RH95% Max    |  |
| Power Source          | DC12V±10%, 550mA           |  |
| Dimension             | 160.8(W) x 62(H) x 62(D)mm |  |
| Weight                | 380g                       |  |