



XVR-7916GDV 16 Channels H.264 DVR

Pentabrid XVR Compatible with AHD/TVI/CVI/CVBS Cameras



■ Features

16CH 720P/1080N 4 in 1 DVR

Support VGA, HDMI full HD output simultaneously;

Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;

Support web, CMS, center platform management software XMEYE.

Support various mobile monitoring (iPhone, Android);

Remote Access, With DNS (ARSP), easy to monitor remotely

Support UTC, control signal & video stream transmit through one single coaxial

Support AHD/TVI/CVI/CVBS Cameras

■ Full Description

Model		XVR-7916GDV
System	Main processor	Hi3521A
Interface	Preview	1/4/8/9/16
Video	Codec	H.264
	Monitor quality	VGA, HDMI: HD
	Preview ability	16*1080N
	Encode ability	16*1080N@12fps/16*960H/8*1080N
	Decode ability	16*1080N@12fps/8*960H/8*1080N
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	16ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner

External Interface	Video input	16ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	2 Channels Audio In / 1 Channel Audio Out
	Alarm I/O	No
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	No
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
	General	Power supply
Power Consumption		<15W (without HDD)
Working environment		Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
Dimension		380*300*55mm
Weight		5Kg